

FDA High Performance Seals' Food & Dairy Compounds



FDA FOOD CONTACT

All compounds comply with the formulation requirements specified in the Code of Federal Regulations Title 21 Part 177 Section 177.2600 "Rubber Articles Intended for Repeated Use."

Dry Foods Only: RTD has over 64 different dry food formulated compounds in multiple different durometers and colors. See www.highperformanceseals.com/fda for a full FDA compound list.

- C-7014: 70 durometer neoprene
- E-7010: 70 durometer EPDM, peroxide cured
- E-7014: 70 durometer EPDM
- E-7018: 70 durometer EPDM, internally lubricated
- E-7019: 70 durometer white EPDM
- E-7020: 70 durometer EPDM, NSF* 61 peroxide cured
- E-7026: 70 durometer blue EPDM
- E-7030: 70 durometer purple EPDM
- E-7033: 70 durometer EPDM, high tear strength
- E-7039: 70 durometer purple EPDM, NSF* 61
- F-7014: 75 durometer black Viton™
- FB-7014: 70 durometer brown Viton™
- FF-7014: 70 durometer Viton™

- N-7027: 70 durometer NBR, low compression set
- N-7041: 70 durometer white NBR
- N-7044: 70 durometer NBR, internally lubricated
- N-7046: 70 durometer NBR, high ACN content
- N-7051: 70 durometer red NBR
- S-7008: 70 durometer silicone, NSF* 61

Dry and Aqueous Foods: Tested against FDA deionized water extraction requirements.

- E-7013: 70 durometer EPDM, NSF* 61
- N-7039: 70 durometer NBR, NSF* 61

All Food Contact Types (dry, aqueous, milk/edible oil and fatty foods): Tested against FDA extraction requirements in deionized water and n-Hexane.

- E-7042: 70 durometer grey EPDM
- F-7044: 75 durometer black Viton™
- F-7045: 75 durometer green Viton™
- N-7086: 70 durometer NBR
- S-7001: 70 durometer silicone*
- S-7004: 70 durometer silicone, NSF*
- S-7020: 70 durometer translucent silicone

* Denotes a stocked compound

3-A SANITARY TESTED

High Performance Seals offers several compounds that have been tested against the 3-A Sanitary Specification 18-03, "3-A Sanitary Standards for Multiple-Use Rubber and Rubber-Like Materials Used as Product Contact Surfaces in Dairy Equipment."

The materials below are classified by maximum service temperature.

Max Service Temperature of 300°F

- F-7044: 75 durometer black Viton™, Class I - IV
- F-7045: 75 durometer green Viton™, Class I - IV
- N-7086: 70 durometer NBR, Class I - IV
- S-7020: 70 durometer clear silicone, Class I - IV

Max Service Temperature of 120°F

- E-7042: 70 durometer grey EPDM, Class III & IV

All of the above compounds are formulated to meet FDA food contact guidelines, including formulation requirements for milk and edible oil. In addition to testing against 3-A, all of these compounds have been tested against FDA deionized water and n-Hexane extraction requirements.

*NSF compounds are manufactured by RT Dygert.



Viton™ is a trademark of The Chemours Company FC, LLC, used under license by High Performance Seals/RT Dygert.



HIGH PERFORMANCE SEALS
An RT Dygert Company

Why Industry Leaders Rely on High Performance Seals

THE HIGHEST STANDARDS

There's no room for compromise when it comes to public health and safety. High Performance Seals meets and exceeds industry standards, and even when standards are voluntary, we hold ourselves to the highest demands.

A TRUSTED LEADER IN FOOD AND DAIRY

For decades High Performance Seals has been an industry forerunner in food & beverage, milk, water, food processing, plumbing, chemical processing and other markets where seals and custom rubber products are crucial.

WE'VE GOT WHAT YOU NEED

We source and stock the widest selection of seals from the finest manufacturers around the world. Our vendors are renowned for their engineering and quality programs and we have excellent, long term relationships with them. Even in periods of short supply, we can deliver. We can customize any seal precisely to your specifications.

EXTENSIVE VALUE ADDED SERVICES

We provide JIT/Kanban programs, pre-production and kitting, special marking and packaging options and much more.

FRIENDLY CUSTOMER SERVICE AND EXPERT ON-PREMISE SUPPORT

You're in the best circles with our customer service team. If you need expertise in any area, we've got it, including materials, design, prototyping, testing and more.



sales@highperformanceseals.com • www.highperformanceseals.com

SEATTLE

3902 W. Valley Hwy N., Suite 200
Auburn, WA 98001
253.218.0123 PHONE
877.796.0123 TOLL FREE
253.218.0121 FAX

MINNEAPOLIS

12121 Nicollet Avenue S.
Burnsville, MN 55337
952.835.1700 PHONE
866.783.8883 TOLL FREE
952.835.1701 FAX

CHICAGO

2700 S. River Road, Suite 116
Des Plaines, IL 60018
847.675.1444 PHONE
800.423.9272 TOLL FREE
847.675.8889 FAX

© 2015, High Performance Seals, Inc. Rev 8.17

LIMITED WARRANTY High Performance Seals ("Seller") warrants that its products ("Goods") will perform in accordance with their specifications; that the goods will be free from manufacturing defects for a period of twelve (12) months from the date of delivery of the goods to Buyer; and that the goods will be as specified by Buyer in the purchase order. Seller should have the right to elect to either refund the purchase price for any defective goods or replace any defective goods, provided that the goods were used in the manner for which they were manufactured. Seller does not warrant that the goods are fit for any particular purpose. Seller should have no obligation to refund the purchase price or replace goods that are rendered defective by a Buyer or a third party after they leave Seller's place of shipment.

LIMITED LIABILITY Seller's liability for its goods is limited to their terms set forth in Seller's express warranty set for above, in no event shall Seller's liability exceed the total purchase order price. Seller is not assuming any liability for any indirect, collateral, special, incidental or consequential losses or damages suffered by Buyer, or by any end-user or other third party, including but not limited to, lost profits, loss of business reputation and/or lost business opportunity, for any possible cause of action or claim arising out of or related to the goods sold to Buyer, even if Seller has been advised of the possibility of such loss or damage.